


# CMO



# Electropompes de surface CMO

## horizontales multicellulaires

### CARACTÉRISTIQUES - 2 pôles 50 Hz

Turbine radiale 	Code	Version	P2		A	µF	DNM	Q m <sup>3</sup> /h l/min	Débit							Dimensions (mm)				Poids kg
			hp	kW					0	20	30	50	70	90	110	A	B	C	D	
<b>SERIE 70</b>																				
CMO 3/70	EM70/030/1	230 V	Monophasé	0,75	0,55	3,44	16	1"¼	40	37	35	27	15			398	163	219	186	13
CMO 4/70	EM70/040/1	230 V	Monophasé	1	0,75	4,78	20	1"¼	54	49	47	36	20			419	184	240	186	14,2
CMO 5/70	EM70/050/1	230 V	Monophasé	1,25	0,92	6,12	25	1"¼	67	62	58	45	25			440	205	261	187	15,2
<b>SERIE 110</b>																				
CMO 4/110	EM110/040	230 V	Monophasé	1,25	0,92	6,12	25	1"	41		39	37	33	26	17	458	228	279	186	15,1
CMO 5/110	EM110/050	230 V	Monophasé	1,5	1,1	7,08	25	1"	53		51	47	41	34	24	527	276	328	197	17

#### FOURNIES AVEC

Condensateur

