


CMO



Electropompes de surface CMO

horizontales multicellulaires

CARACTÉRISTIQUES - 2 pôles 50 Hz

Turbine radiale 	Code	Version	P2		A	µF	DNM	Q m ³ /h l/min	Débit							Dimensions (mm)				Poids kg	
			hp	kW					0	20	30	50	70	90	110	A	B	C	D		
																					H (m)
SERIE 70																					
CMO 3/70	EM70/030/1	230 V	Monophasé	0,75	0,55	3,44	16	1"¼		40	37	35	27	15			398	163	219	186	13
CMO 4/70	EM70/040/1	230 V	Monophasé	1	0,75	4,78	20	1"¼	H	54	49	47	36	20			419	184	240	186	14,2
CMO 5/70	EM70/050/1	230 V	Monophasé	1,25	0,92	6,12	25	1"¼		67	62	58	45	25			440	205	261	187	15,2
SERIE 110																					
CMO 4/110	EM110/040	230 V	Monophasé	1,25	0,92	6,12	25	1"	H	41		39	37	33	26	17	458	228	279	186	15,1
CMO 5/110	EM110/050	230 V	Monophasé	1,5	1,1	7,08	25	1"		53		51	47	41	34	24	527	276	328	197	17

FOURNIES AVEC

Condensateur

